

xOut 4

- Audio output (D/A) expander for SymNet systems that capitalizes on the surplus DSP of a Dante-enabled Symetrix DSP unit to bring overall system costs down.
- 4 line outputs with the industry leading performance specifications of Edge and Radius.
- Configured with Symetrix Composer. No third party software, archaic DIP switches, or complicated front panel menus.
- Network audio expansion using Dante protocol over standard IT networks. Ultra low latency.
- PoE injector included. Rack mount and surface mount kits sold separately.


The cost effective SymNet xOut 4 increases a system's analog output channel capacity resulting in a reduction in overall price per channel. Designed exclusively for use with Dante-enabled Symetrix DSP units, each of the four analog outputs' parameters (mute), along with bus assignments, are configured using Symetrix Composer open architecture software. xOut 4 set up is logical and fast with no requirement to use third party software; there are no mechanical switches or circuit board jumpers to set. Systems are simpler, cost less, and have fewer potential points of failure. A half-rack form factor conserves rack space, or, if preferred, the xOut 4 may be surface mounted.

Specifications

ANALOG OUTPUTS	
Frequency Response	20 Hz – 20 kHz, ± 0.5 dB.
Channel Separation	> 111 dB @ 1 kHz, +24 dBu.
Connectors	3.5 mm Phoenix® connectors.
Number of outputs	Four (4) balanced line level.
Nominal output level	+4 dBu with 20 dB of headroom.
Maximum output level	+24 dBu (+22.8 dBu into a 2k Ohm minimum load).
Output impedance	300 Ohms balanced, 150 Ohms unbalanced.
Dynamic range	> 118 dB, A-weighted.
THD + Noise	< -105 dB, unweighted; 1 kHz @ +22 dBu with 0 dB gain.
Latency	0.60 mS.
SYSTEM	
Sampling Rate	48 kHz, ± 100 ppm.
Dante Cable	Standard CAT6, maximum device-to-device length = 100 meters.

Copyright 2015, Symetrix, Inc. All Rights Reserved. All specifications and features subject to change without notice.

6408 216th Street SW | Mountlake Terrace, WA 98043 USA
T +1.425.778.7728 **F** +1.425.778.7727 | **www.symetrix.co**



1 **Dante (Primary):** 100 Base-T Ethernet port provides 8 (4x4) channels of Dante network audio, Ethernet communications, and power.

2 **Analog Line Outputs:** Four (4) balanced analog line level audio outputs with emergency mute.

Mechanical Specifications

Items	Specifications	Remarks
Space Required	Half rack unit (WDH: 20.83 cm x 22.86 cm x 4.37 cm / 8.2 in. x 9 in. x 1.72 in.) Depth does not include connector allowance.	Allow at least 3 inches additional clearance for rear panel connections. Additional depth may be required depending upon your specific wiring and connections.
Electrical	PoE IEEE 802.3af Class 0, 10 Watts maximum.	No line voltage switching required (100-250 VAC, 50-60 Hz).
Ventilation	Maximum recommended ambient operating temperature is 30 C / 86 F.	Ensure that the left and right equipment sides are unobstructed (5.08 cm, 2 in minimum clearance). The ventilation should not be impeded by covering the ventilation openings with items such as newspapers, tablecloths, curtains, etc.
Certifications or Compliance	UL 60065, cUL 60065, IEC 60065, FCC 15.109:2015, FCC 15.109(g):2015, FCC 15.107:2015, (CISPR 32), EN 55032:2012, EN 55103-2:2009, EN 61000-3-3:2013, EN 61000-3-2:2006, ICES-003:2012, RoHS.	
Shipping Weight	4.4 lbs. (2.0 kg)	

Architect and Engineer Specifications: xOut 4.

The half rack device shall provide four analog line outputs. Levels shall be controllable via DSP modules in software. Audio connections shall be accessed via rear panel 3.5 mm Phoenix® connectors.

Network audio expansion shall be provided by the Dante protocol. The connector shall be 100 Base-T RJ45 utilizing CAT6 cable.

A designer software application shall be provided that operates on a Windows computer, with network interface installed, running Windows® 7 or higher operating system. Computer connection for configuration shall be via a hosting DSP unit's rear panel Ethernet connector that communicates with the devices via Dante.

The front panel shall include indicators for POWER, ETHERNET, and DANTE.

Audio conversion shall be 24-bit, 48 kHz and the dynamic range shall not be lower than 115 dB, A-weighted with a maximum output level of +24 dBu.

The device shall be powered over Ethernet (PoE) by an included 802.3af Class 0 PoE injector. The device shall meet UL/CSA and CE safety requirements and comply with CE and FCC Part 15 emissions limits. The device shall be RoHS compliant. The chassis shall be constructed of cold rolled steel, and may be surface mounted or mount into a standard 19" 1U EIA rack using available mounting kits. The device shall be a **Symetrix xOut 4**.

Copyright 2015, Symetrix, Inc. All Rights Reserved. All specifications and features subject to change without notice.

6408 216th Street SW | Mountlake Terrace, WA 98043 USA
T +1.425.778.7728 **F** +1.425.778.7727 | **www.symetrix.co**