TOA

SPEAKER SYSTEM HX-7W

■DESCRIPTION


The HX-7W is a 2-way compact speaker system that permits both constant directivity control over a wide frequency range and changes in vertical directivity. It adopted wave front control technology is ideal for reproducing clear sound in spaces with long reverberation times or high background noise. The HX-7W is designed for indoor use.

■SPECIFICATIONS


Enclosure	Bass-reflex type
Power Handling Capacity	Continuous pink noise: 250 W (IEC60268-5: 350 W) Continuous program: 750 W
Rated Impedance	8 Ω
Sensitivity	100 dB (1 W, 1 m)
Frequency Response	75 Hz – 20 kHz
Crossover Frequency	1.7 kHz
Directivity Angle	Horizontal: 100° Vertical: Depending on directivity angle mode
Speaker Component	Low frequency: 13 cm (5.5") cone-type × 8 High frequency: Wave front control horn with compression driver × 4
Input Terminal	Speakon NL4MP × 2 and M4 screw terminal, distance between barriers: 9 mm (0.35")
Finish	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white, paint Hanging bracket: Steel plate, t3.0, white, paint
Dimensions	497 (W) × 664 (H) × 274 (D) mm (19.57" × 26.14" × 10.79")
Weight	30 kg (66.14 lb)
Accessory	Hanging bracket L, R (L and R are symmetrical to each other.) ···1 each, Hanging bracket mounting bolt ···4
Option	Matching transformer: MT-200 (*1) Matching Transformer Adapter: HY-MT7 Speaker mounting bracket: HY-60DW, HY-CN7W, HY-PF7W, HY-VM7W, HY-WM7W (*2), HY-C0801W (*2) Speaker stand adapter: HY-ST7

(*1) When mounting the MT-200 Matching Transformer to the speaker, an optional HY-MT7 Matching Transformer Adapter is required.
(*2) HY-VM7W Speaker Mounting Bracket is separately required.


■APPEARANCE (Factory-preset: 0° mode)




Top View



Front View



Side View



Rear View

UNIT: mm SCALE: 1/10

TOA Corporation

DWG No: GHX00AA1


TOA

SPEAKER SYSTEM


HX-7W

■APPEARANCE


Example for directivity angle modes




45° mode



30° mode





15° mode



60° mode


Note:
To set the speaker angle mode to "60° mode," 3 pieces of the optional HY-60DW Speaker Angle Brackets are required.






Enlarged figure for the hanging bracket (accessory)
(scale: 1/6)

Example for hanging bracket mounting
(scale: 1/15)



Hanging vertically



Hanging horizontally

UNIT: mm SCALE: 1/10

TOA Corporation

DWG No: GHX00AC1