Line Array Systems	WPM / WPC / WPS	Link
Torus Line Array Systems	T1215 / T1230 / T820	Link
	Zubehör zu T12xx / T820	Link
FlexPoint	2-Weg System ab 4” bis 15”, (passiv)	Link
TH Series	THH / THV / THS	Link
Subwoofers	passiv	Link
	aktiv	Link
Stage Monitors	LE100 / LE200 / XE300 / XE500	Link
BlacklineX / XP Series (passiv, aktiv)	2-Weg System ab 8” bis 15”, (passiv)	Link
	2-Weg System ab 12”, 15”, (aktiv)	Link
	Zubehör	Link
O-Line (Line Array Installation)	Line Array	Link
CDD Series (passiv, aktiv)	2-way System ab 5.25” bis 15”, schwarz/weiss (passiv)	Link
	Zubehör zu CDD Serie	Link
	DSP und Dante 8”, 12”, 15”, schwarz/weiss (aktiv)	Link
Adorn Series	2-way System 4“ und 5”, schwarz/weiss	Link
Ceiling Series	Deckenlautsprecher	Link
Amplifiers	iKON Serie / VIA	Link
Controllers	DX-Serie	Link

* GoWild (kein BOSE) Artikel

Ersetzt alle bisherigen Preislisten.
Remplace et annule les précédentes listes de prix.

Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.
Articles avec code client gris sont des nouveautés ou ont changé de prix.

Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!
Articles avec code client souligné demandez leur disponibilité!

GoWild AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Wavefront Precision Series

	**WPM**	2-way, passive line array element, LF: 2x6.5” / HF: 3x1.4”, 16Ohm, frequency response 76Hz-18kHz +/- 3dB, max. SPL 130dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)500mm x (H)185mm x (D)377mm, 14Kg	C3	3'430.–
	WPM-W	Dito, **white**	C3	3'430.–
	**WPS**	3-way, passive line array element, LF: 2x8” / MF: 4x4" / HF: 4x 1”, 6Ohm, frequency response 70Hz-18kHz +/- 3dB, max. SPL 133dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)650mm x (H)261mm x (D)400mm, 27Kg	C3	4'885.–
	WPS-W	Dito, **white**	C3	4'885.–
	**WPC**	3-way, bi-amp line array element, LF: 2x10” / MF: 2x5" / HF: 4x 0.7”, 8Ohm, frequency response 65Hz-18kHz +/- 3dB, max. SPL 135dB, 100° hor. / 10° vert, side pocket handles, rear grip handles, (W)772mm x (H)319mm x (D)421mm, 35Kg	C3	6'270.–
	WPC-W	Dito, **white**	C3	6'270.–
	**WPL**	3-way, bi-amp line array element, LF: 2x12” / MF: 2x6.5" / HF: 3x 1”, 8Ohm, frequency response 52Hz-18kHz +/- 3dB, max. SPL LF: 135dB / MF: 140dB / HF: 145dB, 90° hor. / 7.5° vert, side pocket handles, (W)1136mm x (H)371mm x (D)526mm, 64Kg	C3	11'880.–

Diverses Zubehör wie: Tour/Install Flybar, Dolly System, Transition Frame etc. auf Anfrage!

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Torus

	**T820**	2-way, passive, 20° fixed angle array cabinet, LF: 8” / HF: 2x1”, 200W AES @8Ohm, frequency response 70Hz-18kHz +/- 3dB, max. SPL 126dB, 120° hor. / 20° vert, (W)500mm x (H)257mm x (D)320mm, 14Kg	C3	2'640.–
	**T1215**	2-way, passive, 15° fixed angle array cabinet, LF: 12” / HF: 3x1”, 400W AES @8Ohm, frequency response 65Hz-18kHz +/- 3dB, max. SPL 134dB, 60/75/90° hor. / 15° vert, (W)650mm x (H)369mm x (D)452mm, 31Kg	C3	4'290.–
	**T1230**	2-way, passive, 30° fixed angle array cabinet, LF: 12” / HF: 3x1”, 400W AES @8Ohm, frequency response 65Hz +/- 3dB, max. SPL 132dB, 60/75/90° hor. / 30° vert, (W)650mm x (H)350mm x (D)442mm, 26Kg	C3	4'290.–

Torus - Accessories

	**POLERIG20**	Pole-mount bracket for T8xx cabinets	C3	495.–
	POLERIG1530	Pole-mount bracket for T12xx cabinets	C3	530.–
	**SBAR40**	Flying Bracket for up to two T8xx or a single T12xx	C3	265.–
	**HRIG100**	Modular flying bar for horizontal arrays, maximum 3x T8xx or 3x T12xx	C3	660.–
	**GSRIG20**	Ground-stack frame for T8xx cabinets to SXCF115	C3	1'055.–
	GSRIG1530	Dito, for T12xx cabinets to SXCF118	C3	1'715.–
	**T8GRID**	Flying frame for T8xx arrays and transition frame for SXCF115 to T8xx array	C3	3'300.–
	**T12GRID**	Flying frame for T12xx arrays	C3	3'960.–
	**T12TRIG**	Transition frame for SXCF118 to T12xx array	C3	2'310.–
	**T8PB**	Simple rigging bar for T8 cabinet	C3	990.–
	**T12PB**	Simple rigging bar for T12 cabinet	C3	1'055.–
	**ASF20071**	Wind-up telescopic pole for T8xx and T12xx cabinet	C3	295.–

Lautsprecher sowie Zubehör auch in weiss erhätlich!

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

FlexPoint

	**FP4**	2-way, passive, coaxial, miniature point source loudspeaker, LF: 4" / HF: 1.25", 60W AES @16Ohm, frequency response 142Hz-18kHz +/- 3dB, max. SPL 102dB, 110° concial, M6 inserts, (W)130mm x (H)130mm x (D)126mm, 1.9Kg	C3	595.–
	**FP6**	2-way, passive, coaxial, compact point source loudspeaker, LF: 6" / HF: 1.75", 150W AES @16Ohm, frequency response 73Hz-20kHz +/- 3dB, max. SPL 113dB, 100° hor. / 80° vert (user-rotatble), M10 / M6 inserts, (W)321mm x (H)220mm x (D)197mm, 5.5Kg	C3	1'055.–
	**FP8**	2-way, passive, coaxial, compact point source loudspeaker, LF: 8" / HF: 2", 250W AES @8Ohm, frequency response 63Hz-18kHz +/- 3dB, max. SPL 118dB, 90° hor. / 70° vert (user-rotatble), M10 / M6 inserts, (W)376mm x (H)280mm x (D)265mm, 9.3Kg	C3	1'715.–
	**FP12**	2-way, passive, coaxial, compact point source loudspeaker, LF: 12" / HF: 3", 350W AES @8Ohm, frequency response 55Hz-20kHz +/- 3dB, max. SPL 122dB, 90° hor. / 60° vert (user-rotatble), M10 / M6 inserts, (W)521mm x (H)390mm x (D)346mm, 17.5Kg	C3	2'640.–
	**FP15**	2-way, passive, coaxial, compact point source loudspeaker, LF: 15" / HF: 3.5", 500W AES @8Ohm, frequency response 50Hz-20kHz +/- 3dB, max. SPL 126dB, 80° hor. / 50° vert (user-rotatble), M10 / M8 inserts, (W)601mm x (H)460mm x (D)420mm, 27.4Kg	C3	3'300.–

FlexPoint - Accessories

	**FP4Y-B**	FP4 Touring & Install Yoke	C3	65.–
	**FP6YLT-B**	FP6 Landscape Touring Yoke	C3	330.–
	FP8YLT-B	Dito, FP8	C3	395.–
	FP12YLT-B	Dito, FP12	C3	460.–
	FP15YLT-B	Dito, FP15	C3	595.–
	**FP6YPT-B**	FP6 Portrait Touring Yoke	C3	330.–
	FP8YPT-B	Dito, FP8	C3	395.–
	FP12YPT-B	Dito, FP12	C3	460.–
	FP15YPT-B	Dito, FP15	C3	595.–
	**FP6YLI-B**	FP6 Landscape Install Yoke	C3	265.–
	FP8YLI-B	Dito, FP8	C3	330.–
	FP12YLI-B	Dito, FP12	C3	395.–
	FP15YLI-B	Dito, FP15	C3	530.–
	**FP6YPI-B**	FP6 Portrait Install Yoke	C3	265.–
	FP8YPI-B	Dito, FP8	C3	330.–
	FP12YPI-B	Dito, FP12	C3	395.–
	FP15YPI-B	Dito, FP15	C3	530.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

O-Line 4 Pack

	**O-Line**	2 x 3.5" scalable, 2-way, micro-line array, 4 cabinet array (Picture: 2 x Omniline 4 pack - price per 4-pack!) Tech. spec. per module: 50W AES, 200W peak, 84-92 dB 1W/1m, 100° hor., 5° vert., 16Ω, light grey Tech. spec. per 4 pack: 200W AES, 800W peak, 96dB 1W/1m, 4Ω, 14.4kg	C3	2'840.–

Accessories

	**ASF20023**	Flying Bracket	C3	460.–
	**ASF20021**	Wall Bracket for 1 x 4-Pack O-Line Array	C3	530.–
	**ASF20022**	Wall Bracket for 2-3 x 4-Pack O-Line Arrays	C3	1'055.–

TH Series

	**THH**	3-way, bi-amp trapezoid hybrid fully horn loaded, LF: 15" / MF: 10" / HF: 1", LF: 750W AES @8Ohm, MF+HF: 300W AES @8Ohm, frequency response 50Hz-18kHz +/- 3dB, max. SPL 133dB, 70° hor. / 40° vert, pocket handle, M10 inserts, (W)1067mm x (H)558mm x (D)780mm, 77Kg	C3	5'940.–
	THV	Dito, **Vertical**	C3	5'940.–
	**THS**	3-way, bi-amp triaxial point source loudspeaker, LF: 15" / MF: 1.4" / HF: 1.4", LF: 800W AES @8Ohm, MF+HF: 110W AES @8Ohm, frequency response 54Hz-18kHz +/- 3dB, max. SPL 129dB, 85° hor. / 50° vert, pocket handle, M10 inserts, (W)511mm x (H)710mm x (D)511mm, 35.6Kg	C3	4'620.–
	**THSYLT-B**	Landscape Touring Yoke	C3	660.–
	THSYLI-B	Landscape Install Yoke	C3	595.–
	**THSYPT-B**	Portrait Touring Yoke	C3	725.–
	THSYPI-B	Portrait Install Yoke	C3	595.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Stage Monitors

	**LE100**	2-way, passive coaxial differential dispersion, LF: 12" / HF: 1", 300W AES @8Ohm, frequency response 78Hz-20kHz +/- 3dB, max. SPL 129dB, 110° hor. / 60° vert, pocket handle, M8 inserts, pole mounting, protective rubber feet (W)490mm x (H)302mm x (D)472mm, 18Kg	C3	1'980.–
	**LE200**	2-way, passive coaxial differential dispersion, LF: 15" / HF: 1.4", 400W AES @8Ohm, frequency response 78Hz-20kHz +/- 3dB, max. SPL 133dB, 110° hor. / 60° vert, pocket handle, M8 inserts, pole mounting, protective rubber feet (W)610mm x (H)364mm x (D)562mm, 26Kg	C3	2'375.–
	**XE300**	2-way, passive/bi-amp coaxial differential dispersion, LF: 12" / HF: 1.4", LF: 350W AES @6Ohm, HF: 80W AES @8Ohm, frequency response 67Hz-18kHz +/- 3dB, max. SPL 139dB, 60° hor. / 90° vert, pocket handle, M8 inserts, protective rubber feet, (W)550mm x (H)290mm x (D)470mm, 19Kg	C3	3'300.–
	**XE500**	2-way, passive/bi-amp coaxial differential dispersion, LF: 15" / HF: 1.4", LF: 550W AES @4Ohm, HF: 80W AES @8Ohm, frequency response 62Hz-18kHz +/- 3dB, max. SPL 143dB, 60° hor. / 70° vert, bar handles, M8 inserts, protective rubber feet, (W)635mm x (H)364mm x (D)583mm, 19Kg	C3	4'355.–

CDD Live – aktiv

	**CDD-LIVE8B**	2-way, powerd ultra-compact coaxial differential dispersion system, LF: 8" / HF: 1", peak 1300W, continuous 650W, frequency response 70Hz-20kHz +/- 3dB, max. SPL 123dB, 110° hor. / 60° vert, (user-rotatble), pocket handle, M8 inserts, pole mounting, (W)258mm x (H)428mm x (D)254mm, 14Kg, **Dante, DSP**	C3	2'905.–
	CDD-LIVE8W	Dito, **white**	C3	2'905.–
	**CDD-LIVE12B**	2-way, powerd ultra-compact coaxial differential dispersion system, LF: 12" / HF: 1", peak 2500W, continuous 1250W, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 110° hor. / 60° vert, (user-rotatble), pocket handle, M8 inserts, pole mounting, (W)359mm x (H)580mm x (D)373mm, 28Kg, **Dante, DSP**	C3	3'695.–
	CDD-LIVE12W	Dito, **white**	C3	3'695.–
	**CDD-LIVE15B**	2-way, powerd ultra-compact coaxial differential dispersion system, LF: 15" / HF: 1.4", peak 2500W, continuous 1250W, frequency response 55Hz-20kHz +/- 3dB, max. SPL 132dB, 110° hor. / 60° vert, (user-rotatble), pocket handle, M8 inserts, pole mounting, (W)427mm x (H)696mm x (D)422mm, 37Kg, **Dante, DSP**	C3	4'620.–
	CDD-LIVE15W	Dito, **white**	C3	4'620.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

CDD Live – Accessories

	**CDDCB6/8B**	Ceiling bracket for CDD-Live 8, **black**	C3	200.–
	CDDCB6/8W	Dito, **white**	C3	200.–
	**WB6/8B**	Wall bracket for CDD-Live 8, **black, weatherised**	C3	75.–
	WB6/8W	Dito, **white**	C3	75.–
	**WB10/12B**	Wall bracket for CDD-Live 12, **black, weatherised**	C3	85.–
	WB10/12W	Dito, **white**	C3	85.–
	**CDDLUB8B**	Universal bracket for CDD-Live 8, **black**	C3	330.–
	**ASF20046**	Universal bracket for CDD-Live 12, **black**	C3	595.–
	ASF20048	Universal bracket for CDD-Live 15, **black**	C3	595.–
	**CDDLYA8B**	Yoke assembly for CDD-Live 8, **black**	C3	330.–
	CDDLYA8W	Dito, **white**	C3	330.–
	CDDLYA12B	Yoke assembly for CDD-Live 12, **black**	C3	345.–
	CDDLYA12W	Dito, **white**	C3	345.–
	CDDLYA15B	Yoke assembly for CDD-Live 15, **black**	C3	395.–
	CDDLYA15W	Dito, **white**	C3	395.–
	**HTKCT05**	8mm shouldered eye bolt for CDD-Live 8, 12, 15	C3	40.– (Stück)
	**ASF20045**	Universal 35mm pole mount adaptor	C3	65.–
	**ASF20071**	Wind-up telescopic pole	C3	295.–

Diverses Zubehör wie: Transit Cover, Rain Kit Upgrade auf Anfrage!

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

CDD Series – passiv

			VPE		
	**CDD5B**	2-way, passive ultra compact differential dispersion system, LF: 5.25” / HF: 0.75”, 100W AES @8Ohm, frequency response 100Hz-20kHz +/- 3dB, max. SPL 116dB, 120° hor. / 80° vert, (user-rotatble), M6 inserts, (W)160mm x (H)230mm x (D)149mm, 3Kg, **incl. wall bracket**	2	C3	275.–
	CDD5W	Dito, **white**	2	C3	275.–
	CDD5BTX-WR	Dito, 6/12.5/25W@100V, **black, weatherised**	2	C3	335.–
	CDD5WTX-WR	Dito, 6/12.5/25W@100V, **white, weatherised**	2	C3	335.–
	CDD5BTX-MAR	For cruise ships and seaside resort applications, **black**	2	C3	475.–
	CDD5WTX-MAR	Dito, **white**	2	C3	475.–
	**CDD6B**	2-way, passive ultra compact differential dispersion system, LF: 6.5” / HF: 1”, 150W AES @8Ohm, frequency response 80Hz-20kHz +/- 3dB, max. SPL 119dB, 110° hor. / 80° vert, (user-rotatble), M6 inserts, (W)210mm x (H)325mm x (D)210mm, 5.7Kg	2	C3	460.–
	CDD6W	Dito, **white**	2	C3	460.–
	CDD6BTX-WR	Dito, 12.5/25/50W@100V, **black, weatherised**	2	C3	530.–
	CDD6WTX-WR	Dito, 12.5/25/50W@100V, **white, weatherised**	2	C3	530.–
	CDD6BTX-MAR	For cruise ships and seaside resort applications, **black**	2	C3	740.–
	CDD6WTX-MAR	Dito, **white**	2	C3	740.–
	**CDD8B**	2-way, passive ultra compact differential dispersion system, LF: 8” / HF: 1”, 200W AES @8Ohm, frequency response 70Hz-20kHz +/- 3dB, max. SPL 119dB, 110° hor. / 60° vert, (user-rotatble), M6 inserts, (W)256mm x (H)410mm x (D)252mm, 9.5Kg		C3	890.–
	CDD8W	Dito, **white**		C3	890.–
	CDD8B-WR	Dito, **black, weatherised**		C3	1'100.–
	CDD8W-WR	Dito, **white, weatherised**		C3	1'100.–
	CDD8BTX	Dito, 15/30/60/120W@100V, 11.1Kg, **black**		C3	1'025.–
	CDD8WTX	Dito, **white**		C3	1'025.–
	CDD8BTX-WR	Dito, **black, weatherised**		C3	1'220.–
	CDD8WTX-WR	Dito, **white, weatherised**		C3	1'220.–
	CDD8BTX-MAR	For cruise ships and seaside resort applications, **black**		C3	1'520.–
	CDD8WTX-MAR	Dito, **white**		C3	1'520.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

	**CDD10B**	2-way, passive ultra compact differential dispersion system, LF: 10” / HF: 1”, 250W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 126dB, 110° hor. / 60° vert (user-rotatble), M6 inserts, (W)323mm x (H)513mm x (D)310mm, 15.3Kg	C3	1'320.–
	CDD10W	Dito, **white**	C3	1'320.–
	CDD10B-WR	Dito, **black, weatherised**	C3	1'650.–
	CDD10W-WR	Dito, **white, weatherised**	C3	1'650.–
	CDD10BTX	Dito, 15/30/60/120W@100V, 16.9Kg, **black**	C3	1'520.–
	CDD10WTX	Dito, **white**	C3	1'520.–
	CDD10BTX-WR	Dito, **black, weatherised**	C3	1'850.–
	CDD10WTX-WR	Dito, **white, weatherised**	C3	1'850.–
	CDD10BTX-MAR	For cruise ships and seaside resort applications, **black**	C3	2'375.–
	CDD10WTX-MAR	Dito, **white**	C3	2'375.–
	**CDD12B**	2-way, passive ultra compact differential dispersion system, LF: 12” / HF: 1”, 300W AES @8Ohm, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 110° hor. / 60° vert (user-rotatble), M8 inserts, (W)360mm x (H)560mm x (D)350mm, 19Kg	C3	1'915.–
	CDD12W	Dito, **white**	C3	1'915.–
	CDD12B-WR	Dito, **black, weatherised**	C3	2'180.–
	CDD12W-WR	Dito, **white, weatherised**	C3	2'180.–
	CDD12B-MAR	For cruise ships and seaside resort applications, **black**	C3	3'035.–
	CDD12W-MAR	Dito, **white**	C3	3'035.–
	**CDD15B**	2-way, passive ultra compact differential dispersion system, LF: 15” / HF: 1.4”, 400W AES @8Ohm, frequency response 55Hz-18kHz +/- 3dB, max. SPL 132dB, 110° hor. / 60° vert (user-rotatble), M8 inserts, (W)432mm x (H)685mm x (D)413mm, 19Kg	C3	2'375.–
	CDD15W	Dito, **white**	C3	2'375.–
	CDD15B-WR	Dito, **black, weatherised**	C3	2'770.–
	CDD15W-WR	Dito, **white, weatherised**	C3	2'770.–
	CDD15B-MAR	For cruise ships and seaside resort applications, **black**	C3	3'830.–
	CDD15W-MAR	Dito, **white**	C3	3'830.–

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

CDD Series - Accessories

	**WB6/8B**	Wall bracket for CDD6Bxx – CDD8Bxx, **black, weatherised**	C3	75.–
	WB6/8W	Dito, **white**	C3	75.–
	WB6/8B-MAR	Wall bracket for CDD6BTX-MAR – CDD8BTX-MAR, **black**	C3	395.–
	WB6/8W-MAR	Dito **white**	C3	395.–
	WB10/12B	Wall bracket for CDD10Bxx – CDD12Bxx, **black, weatherised**	C3	85.–
	WB10/12W	Dito **white**	C3	85.–
	WB10/12B-MAR	Wall bracket for CDD10BTX-MAR – CDD12BTX-MAR, **black**	C3	460.–
	WB10/12W-MAR	Dito **white**	C3	460.–
	**CDDCB5B-WR**	Ceiling bracket for CDD5Bxx, **black, weatherised**	C3	95.–
	CDDCB5W-WR	Dito, **white**	C3	95.–
	**CDDCB6/8B-WR**	Ceiling bracket for CDD6Wxx – CDD8Wxx, **black, weatherised**	C3	200.–
	CDDCW6/8W-WR	Dito, **white**	C3	200.–
	**CDDY10B**	Yoke assembly for CDD10Bxx, **black, weatherised**	C3	330.–
	CDDY10W	Dito, **white**	C3	330.–
	CDDY12B	Yoke assembly for CDD12Bxx, **black, weatherised**	C3	395.–
	CDDY12W	Dito, **white**	C3	395.–
	CDDY15B	Yoke assembly for CDD15Bxx, **black, weatherised**	C3	430.–
	CDDY15W	Dito **white**	C3	430.–
	**HTKCT05**	8mm shouldered eye bolt for CDD 10, 12, 15	C3	40.– (Stück)

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

BlacklineX Series – passiv

	**X8B**	2-way, passive ultra compact system, LF: 8” / HF: 1”, 200W AES @8Ohm, frequency response 70Hz-20kHz +/- 3dB, max. SPL 121dB, 90° hor. / 50° vert (user-rotatble), M6/M8 inserts, pocket handle, pole mounting, (W)257mm x (H)422mm x (D)243mm, 8Kg	C3	530.–
	**X10B**	2-way, passive ultra compact system, LF: 10” / HF: 1”, 250W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 124dB, 90° hor. / 50° vert (user-rotatble), M8 inserts, pocket handle, pole mounting, (W)324mm x (H)522mm x (D)289mm, 14Kg	C3	790.–
	**X12B**	2-way, passive ultra compact system, LF: 12” / HF: 1”, 300W AES @8Ohm, frequency response 65Hz-20kHz +/- 3dB, max. SPL 128dB, 80° hor. / 50° vert (user-rotatble), M8 inserts, pocket handle, pole mounting, (W)358mm x (H)574mm x (D)337mm, 17Kg	C3	925.–
	**X15B**	2-way, passive ultra compact system, LF: 15” / HF: 1”, 400W AES @8Ohm, frequency response 55Hz-20kHz +/- 3dB, max. SPL 131dB, 80° hor. / 50° vert (user-rotatble), M8 inserts, pocket handle, pole mounting, (W)427mm x (H)690mm x (D)419mm, 24Kg	C3	1'055.–

BlacklineXP Series – Powered

	**XP12**	2-way, powerd compact system, LF: 12” / HF: 1”, peak 1300W, frequency response 62Hz-20kHz +/- 3dB, max. SPL 128dB, 80° hor. / 50° vert, (user-rotatble), pocket handle, M8 inserts, pole mounting, (W)358mm x (H)574mm x (D)318mm, 18Kg, **DSP**	C3	1'450.–
	**XP15**	2-way, powerd compact system, LF: 15” / HF: 1”, peak 1300W, frequency response 55Hz-20kHz +/- 3dB, max. SPL 131dB, 80° hor. / 50° vert, (user-rotatble), pocket handle, M8 inserts, pole mounting, (W)427mm x (H)690mm x (D)407mm, 26Kg, **DSP**	C3	1'650.–

BlacklineX / XP Series – Accessories

	**WB6/8B**	Wall bracket for X8B, **black, weatherised**	C3	75.–
	WB10/12B	Wall bracket for X10B - X12B - X15B – XP12, **black, weatherised**	C3	85.–
	**HTKCT04**	Pole for BlacklineX	C3	35.–
	**HTKCT05**	8mm shouldered eye bolt for X8, X10, X12, X15	C3	40.– (Stück)

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Adorn – Series

			VPE		
	**A40B**	2-way, passive ultra compact system, LF: 4” / HF: 0.75”, 40W AES @16Ohm, frequency response 98Hz-17kHz +/- 3dB, max. SPL 109dB, 110° hor. / 80° vert, (W)124mm x (H)200mm x (D)144mm, 1.7Kg, **incl. wall bracket**	2	C3	140.–
	A40W	Dito, **white**	2	C3	140.–
	A40TB	Dito, 2.5/5/10W@100V, 2.1Kg, **black**	2	C3	170.–
	A40TW	Dito, **white**	2	C3	170.–
	**A55B**	2-way, passive ultra compact system, LF: 5.25” / HF: 0.75”, 50W AES @16Ohm, frequency response 90Hz-17kHz +/- 3dB, max. SPL 109dB, 110° hor. / 80° vert, (W)152mm x (H)245mm x (D)140mm, 2.1Kg, **incl. wall bracket**	2	C3	185.–
	A55W	Dito, **white**	2	C3	185.–
	A55TB	Dito, 7.5/15/30W@100V, 2.8Kg, **black**	2	C3	225.–
	A55TW	Dito, **white**	2	C3	225.–
	**AIPKIT-B**	IP44 Connector cover for A40 and A55 Series, **black**	2	C3	10.–
	AIPKIT-W	Dito, **white**	2	C3	10.–

Adorn Series – Accessories

	**CDDCB5B-WR**	Ceiling bracket for A40xx – A55xx, **black, weatherised**	C3	95.–
	CDDCB5W-WR	Dito, **white**	C3	95.–

Subwoofer – passiv

	**SX110B**	slimline, direct radiating subwoofer, 10”, 250W AES @8Ohm, frequency response 50Hz-150Hz +/- 3dB, max. SPL 127dB, omnidirectional, M8 inserts, (W)417mm x (H)297mm x (D)415mm, 12Kg	C3	560.–
	SX110W	Dito, **white**	C3	560.–
	**SX210B**	slimline, dual-driver direct radiating subwoofer, 2x 10”, 500W AES @4Ohm, frequency response 50Hz-150Hz +/- 3dB, max. SPL 133dB, omnidirectional, M8 inserts, bar handles, (W)718mm x (H)295mm x (D)465mm, 20Kg	C3	910.–
	SX210W	Dito, **white**	C3	910.–
	**SX112B**	ultra compact, direct radiating subwoofer 12”, 400W AES @8Ohm, frequency response 48Hz-150Hz +/- 3dB, max. SPL 132dB, omnidirectional, M10 inserts, (W)487mm x (H)390mm x (D)410mm, 21.5Kg	C3	1'025.–
	SX112W	Dito, **white**	C3	1'025.–
	SX112-W-MAR	For cruise ships and seaside resort applications, **white**	C3	2'575.–
	**SX212B**	compact, dual-driver direct radiating subwoofer 2x 12”, 800W AES @4Ohm, frequency response 48Hz-150Hz +/- 3dB, max. SPL 138dB, omnidirectional, M10 inserts, (W)872mm x (H)390mm x (D)437mm, 39Kg	C3	1'385.–
	SX212W	Dito, **white**	C3	1'385.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

	**X115B**	compact, direct radiating subwoofer, 15”, 500W AES @8Ohm, frequency response 45Hz-150Hz +/- 3dB, max. SPL 135dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)465mm x (H)590mm x (D)565mm, 27Kg	C3	1'055.–
	**SX115**	compact, direct radiating subwoofer, 15”, 1000W AES @8Ohm, frequency response 45Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, bar handles, pole mounting, provision for castors, (W)500mm x (H)451mm x (D)678mm, 36.5Kg	C3	1'980.–
	**SX215**	compact, dual-driver direct radiating subwoofer, 2x 15”, 2000W AES @8Ohm, frequency response 45Hz-100Hz +/- 3dB, max. SPL 136dB, omnidirectional, provision for castors, (W)961mm x (H)463mm x (D)679mm, 64Kg	C3	2'640.–
	**SXC115**	compact, cardioid subwoofer, 15" 1000W AES @8Ohm, 12" 800W AES @8Ohm, frequency response 44Hz-150Hz +/- 3dB, max. SPL 137dB, cardioid, M10 inserts, bar handles, pole mounting, provision for castors, (W)500mm x (H)550mm x (D)811mm, 53Kg	C3	3'630.–
	SXC115W	Dito, **white**	C3	3'630.–
	SXCF115	Dito, flown, (W)500mm x (H)552mm x (D)810mm, 61Kg	C3	5'610.–
	**X118B**	compact, direct radiating subwoofer, 18”, 500W AES @8Ohm, frequency response 42Hz-150Hz +/- 3dB, max. SPL 137dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)530mm x (H)669mm x (D)640mm, 33Kg	C3	1'320.–
	**SX118B**	compact, direct radiating subwoofer, 18”, 1000W AES @8Ohm, frequency response 47Hz-150Hz +/- 3dB, max. SPL 138dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)600mm x (H)509mm x (D)632mm, 43.5Kg	C3	2'640.–
	SX118W	Dito, **white**	C3	2'640.–
	SX118B-MAR	For cruise ships and seaside resort applications, **black**	C3	3'960.–
	SX118W-MAR	Dito, **white**	C3	3'960.–
	**SXC118B**	compact, cardioid subwoofer, 18" 1000W AES @8Ohm, 14" 800W AES @8Ohm, frequency response 43Hz-150Hz +/- 3dB, max. SPL 140dB, cardioid, M10 inserts, bar handles, pole mounting, provision for castors, (W)650mm x (H)603mm x (D)812mm, 73Kg	C3	4'950.–
	SXC118W	Dito, **white**	C3	4'950.–
	SXCF118B	Dito, flown, (W)650mm x (H)611mm x (D)812mm, 75Kg	C3	6'600.–
	**X218**	dual-driver direct radiating subwoofer, 2x 18”, 1600W AES @4Ohm, frequency response 42Hz-200Hz +/- 3dB, max. SPL 141dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1049mm x (H)587mm x (D)727mm, 88Kg	C3	2'310.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

	**SX218B**	dual-driver direct radiating subwoofer, 2x 18”, 2000W AES @2x 8Ohm, frequency response 35Hz-200Hz +/- 3dB, max. SPL 144dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1093mm x (H)537mm x (D)792mm, 102Kg	C3	5'015.–
	SX218W	Dito, **white**	C3	5'015.–
	SX218B-MAR	For cruise ships and seaside resort applications, **black**	C3	7'655.–
	SX218W-MAR	Dito, **white**	C3	7'655.–
	**SXH218**	hybrid® horn/reflex flown dual-driver subwoofer, 2x 18”, 3000W AES @4Ohm, frequency response 32Hz-200Hz +/- 3dB, max. SPL 148dB, omnidirectional, bar handles, (W)1112mm x (H)609mm x (D)1151mm, 116Kg	C3	8'910.–
	SXHF218	Dito, flown, (W)1148mm x (H)604mm x (D)1155mm, 138Kg	C3	11'220.–

Diverses Zubehör wie: Transit Cover, Rain Kit Upgrade auf Anfrage!

Subwoofer – powerd

	**XP118**	powerd compact direct radiating subwoofer, 18”, peak 2000W, frequency response 52Hz-150Hz +/- 3dB, max. SPL 137dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)600mm x (H)507mm x (D)632mm, 46.5Kg	C3	1'915.–
	**SXP118B**	powerd compact direct radiating subwoofer, 18”, peak 2000W, frequency response 47Hz-150Hz +/- 3dB, max. SPL 135dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)662mm x (H)536mm x (D)640mm, 44Kg, **Dante, DSP**	C3	4'620.–
	SXP118W	Dito, **white**	C3	4'620.–
	**SXP218B**	powerd dual-driver compact direct radiating subwoofer, 2x 18”, peak 4000W, frequency response 35Hz-150Hz +/- 3dB, max. SPL 143dB, omnidirectional, M10 inserts, bar handles, pole mounting, provision for castors, (W)1085mm x (H)537mm x (D)792mm, 101Kg, **Dante, DSP**	C3	6'600.–
	SXP218W	Dito, **white**	C3	6'600.–

Subwoofer – Accessories

	**HTKCT05**	8mm shouldered eye bolt for SX110, SX210, X115,	C3	40.– (Stück)
	HTKCT06	10mm shouldered eye bolt for SX112, SX212, SX118, SXC118, SX218, SXP118, SXP218	C3	45.– (Stück)
	**ASF20071**	Wind-up telescopic pole for SX118, SXC118, SX218, SXP118, SXP218	C3	295.–

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Ceiling Series

			VPE		
	**C4.8T**	2-way, passive high performance ceiling system, LF: 4” / HF: 0.8”, 40W AES @16Ohm, 3/6/12.5/25W@100V, frequency response 100Hz-20kHz +/- 3dB, max. SPL 108dB, 180° conical, cut out 178mm, Ø 205mm x (D)131mm, 2.6Kg	*2*	C3	200.–
	**C6.8T**	2-way, passive high performance ceiling system, LF: 6.5” / HF: 0.8”, 75W AES @16Ohm, 5/10/20/40W@100V, frequency response 90Hz-20kHz +/- 3dB, max. SPL 112dB, 180° conical, cut out 224mm, Ø 260mm x (D)181mm, 3.5Kg	*2*	C3	275.–
	**C8.1T**	2-way, passive high performance ceiling system, LF: 8” / HF: 1”, 125W AES @16Ohm, 7.5/15/30/60W@100V, frequency response 80Hz-18kHz +/- 3dB, max. SPL 116dB, 180° conical, cut out 308mm, Ø 354mm x (D)258mm, 6.7Kg	*2*	C3	395.–
	**ACS-40TS**	2-way, passive ultra compact ceiling system, LF: 4” / HF: 0.75”, 40W AES @16Ohm, 5/10/20@100V, frequency response 106Hz-20kHz +/- 3dB, max. SPL 108dB, 180° conical, cut out 197mm, Ø 221mm x (D)100mm, 2.2Kg	*2*	C3	165.–
	**ACS-55TS**	2-way, passive ultra compact ceiling system, LF: 5.25” / HF: 0.75”, 50W AES @16Ohm, 7.5/15/30@100V, frequency response 117Hz-20kHz +/- 3dB, max. SPL 113dB, 180° conical, cut out 222mm, Ø 245mm x (D)100mm, 2.8Kg	*2*	C3	200.–
	**ACS-55T**	Dito, (D)209mm, 3Kg	*2*	C3	225.–
	**ACP-55TW**	Dito, pendant speaker, **white**		C3	295.–
	ACP-55TB	Dito, pendant speaker, **black**		C3	295.–

Accessories

	**GEB-180T150**	Einbetoniergehäuse mit Einbauöffnung 180mm, Höhe Innen 150mm, Höhe Aussen 165mm, Gewicht 1'160 Gr. Passend zu: Martin Audio C4.8T	*1*	C3	75.–
	GEB-200T150	Einbetoniergehäuse mit Einbauöffnung 200mm, Höhe Innen 150mm, Höhe Aussen 165mm, Gewicht 1'160 Gr. Passend zu: Martin Audio ACS-40TS	*1*	C3	75.–
	GEB-225T180	Einbetoniergehäuse mit Einbauöffnung 225mm, Höhe Innen 180mm, Höhe Aussen 195mm, Gewicht 1'350 Gr. Passend zu: Martin Audio ACS-55TS, Martin Audio C6.8T	*1*	C3	75.–
	**Adorn CK3**	3m cable with carabiner	*2*	C3	35.– (Stück)

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Amplifiers

	**iK42 DANTE**	4 channel Class D amplifier, 20'000 Watts RMS all channels driven, (5000W per channel @ 2Ω) 96kHz DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 8Kg	C3	9'700.–
	**iK81 DANTE**	8 channel Class D amplifier, 10'000 Watts RMS all channels driven (1250W per channel @ 2/4/8Ω) 96kHz DSP inputs and outputs, Analogue, AES3, Ethernet, Dante Powercon™, 12.5Kg	C3	10'495.–
	**VIA2004**	Class D, 4x 500W@4Ω, 4x 250W@8Ω, 8Kg	C3	1'320.–
	**VIA2502**	Class D, 2x 1250W@2Ω, 2x 800W@4Ω, 2x 450W@8Ω, 8Kg	C3	1'980.–
	**VIA5002**	Class D, 2x 2500W@4Ω, 2x 1600W@8Ω, 10Kg	C3	3'300.–
	**VIA5004**	Class D, 4x 1250W@2Ω, 4x 800W@4Ω, 4x 450W@8Ω, 10Kg	C3	3'300.–

Controllers

	**DX4.0 DANTE**	System Controller, 4In / 8Out, AES3, Dante, 1HE	C3	3'630.–
	**DX0.4**	System Controller, 2In / 4Out, Ethernet, USB, 1HE	C3	725.–
	**DX0.6**	System Controller, 2In / 6Out, Ethernet, USB, 1HE	C3	990.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05