Der Vertrieb der PanAcoustics Produkte erfolgt durch den autorisierten Fachhandel. Fragen Sie uns an, wir helfen Ihnen sehr gerne weiter.

Standard colours: RAL 9006 (**aluminium**) or RAL-9010 (**white**) or RAL-9005 (**black**)
Standard delivery is **without mounting** brackets

Pan Beam – PB 04



PB 04	**Standard version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 4 x 3.5"wide band chassis, amplifier output power: 4 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, colour: RAL 9006 aluminium	C3	
PB 04-AES/EBU	As PB 04 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
PB 04-D	As PB 04 but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
PB 04-D-PoE++	As PB 04-D but with PoE Module instead of PSU: 90...264 V AC ****NEUE VERSION****	C3	
PB 04-100V	As PB 04 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
PB 04-100V-DC input	As PB 04 but with 2 x **100V** Input (terminal clamp), addidional **24V DC input**	C3	
PB 04-IP65	AS PB 04 but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 04-100V-IP65	AS PB 04 -100V but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 04-100V-DC-Input-IP65	AS PB 04 -100V-DC Input but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 08



PB 08	**Standard Version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 8 x 3.5" wide band chassis, amplifier output power: 8 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, colour: RAL 9006 aluminium	C3	
PB 08-R	As PB 08 but as **rental version** with PSU: 110V / 230V with TrueCon connector. **Standard colour: RAL 9005 black**	C3	
PB 08-AES/EBU	As PB 08 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
PB 08-D	As PB 08 but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
PB 08-D-PoE++	As PB 08-D but with PoE Module instead of PSU ****NEUE VERSION****	C3	
PB 08-100V	As PB 08 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
PB 08-100V-DC input	As PB 08 but with 2 x **100V** Input (terminal loudspeaker clamp), addidional **24/48V DC input** (cable gland)	C3	
PB 08-IP65	AS PB 08 but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 08-100V-IP65	AS PB 08 -100VI but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 08-100V-DC input-IP65	AS PB 08 -100V-DC Input MKII but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 15 Series (for HQ voice application)

	**PB 15-D**	**Standard version:** Compact active digitally controllable column speaker with Single Beam Steering Technology, Drivers: 15 x 2.1“ wide band chassis, amplifier output power: 8 x up to 50 watt, Pan Beam network I/O: RJ 45 + 2 x RJ 45 (prim/ sec) for Dante, PSU: 110V / 230V with IEC 60320-1 C13 connector, colour: RAL 9006 aluminium	C3	
	PB 15-AES/EBU	As PB 04 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
	PB 15-100V-DC input	As PB 07 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 16



	PB 16	**Standard version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5"wide band chassis, amplifier output power: 16 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 16 consists of two modules with internal link, colour: RAL 9006 aluminium	C3	
	PB 16-AES/EBU	As PB 16 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
	PB 16-D	As PB 16 but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
	PB 16-100V	As PB 16 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
	PB 16-100V-DC input	As PB 16 but with 2 x **100V** Input (terminal loudspeaker clamp), addidional 24/48V DC input (cable gland)	C3	
	PB 16-IP65	AS PB 16 but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
	PB 16-100V-IP65	AS PB 16 -100V but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
	PB 16-100V-DC input-IP65	AS PB 16 -100V-DC Input but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 16 (one housing)

	PB 16 (one housing)	**(one housing) Standard Version:** As PB 16 MKII in **one housing with 2 seperated grills**	C3	
	PB 16-AES/EBU (one housing)	As PB 16 (one housing), EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
	PB 16-D (one housing)	As PB 16 (one housing) with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
	PB 16-100V (one housing)	As PB 16 (one housing) with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
	P 16-100V-DC input MKII (one housing)	As PB 16 (one housing) with 2 x **100V** Input (terminal loudspeaker clamp), additional **24/48V DC input**	C3	

Pan Beam – PB 16-C

	PB 16-C	**Standard Version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 16 x 3.5"wide band chassis, amplifier output power: 16 x up to 40 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 16-C consists of two modules with internal link, colour: RAL 9006 aluminium	C3	
	PB 16-C-AES/EBU	As PB 16-C, EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	

Pan Beam – PB 16-C (one housing)

	PB 16-C (one housing)	**Standard Version:** As PB 16-C in one housing with 2 seperated grills	C3	
	PB 16-C-AES/EBU (one housing)	As PB 16-C (one housing), EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 24



PB 24	**Standard version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 24 x 3.5"wide band chassis, amplifier output power: 24 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 24 consists of three modules with internal link, colour: RAL 9006 aluminium	C3	
PB 24-AES-EBU	As PB 24 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
PB 24-D	As PB 24 but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
PB 24-100V	As PB 24 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
PB 24-100V-DC input	As PB 24 but with 2 x **100V** Input (terminal loudspeaker clamp), addidional **24/48V DC input** (cable gland)	C3	
PB 24-IP65	AS PB 24 but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 24-100V-IP65	AS PB 24 -100V but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 24-100V-DC input-IP65	AS PB 24 -100V-DC Input but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 24 (one housing) Series

	PB 24 (one housing)	**Standard verson:** As PB 24 in one housing with 3 seperated grills	C3	
	PB 24-AES/EBU (one housing)	As PB 24 (one housing) but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
	PB 24-D (one housing)	As PB 24 (one housing) but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 32



PB 32	**Standard version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 32 x 3.5"wide band chassis, amplifier output power: 32 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 32 consists of three modules with internal link, colour: RAL 9006 aluminium	C3	
PB 32-AES/EBU	As PB 32 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
PB 32-D	As PB 32 but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
PB 32-100V	As PB 32 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
PB 32-100V-DC input	As PB 32 with 2 x **100V** Input (terminal clamp), addidional **24/48V DC input**	C3	
PB 32-IP65	AS PB 32I but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 32-100V-IP65	AS PB 32 -100V but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 32-100V-DC input-IP65I	AS PB 32 -100V-DC Input MKII but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 40



PB 40	**Standard version:** Compact active digitally controllable column speaker with Beam Steering Technology, Drivers: 40 x 3.5"wide band chassis, amplifier output power: 40 x up to 100 watt, Pan Beam network I/O: EtherCon RJ 45 for 2x analog line input, controll data and error detection, PSU: 110V / 230V with IEC 60320-1 C13 connector, PB 40 consists of three modules with internal link, colour: RAL 9006 aluminium	C3	
PB 40-AES/EBU	As PB 40 but with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
PB 40-D	As PB 40 but with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	
PB 40-100V	As PB 40 but with 2 x **100V** Input (terminal loudspeaker clamp)	C3	
PB 40-100V-DC input	As PB 40 with 2 x **100V** Input (terminal clamp), addidional **24/48V DC input**	C3	
PB 40-IP65	AS PB 40 but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 40-100V-IP65	AS PB 40 -100V but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	
PB 40-100V-DC input-IP65I	AS PB 40 -100V-DC Input but IP65 weather protection, 3 x bucaneer, powerCON TRUE 1	C3	

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 224



PB 224	**Standard verson:** Compact active digitally controllable 2-way line speaker system, Drivers: 6 x 6.5 "HiQ cone, 18 x 1" HiQ RF neodymium drivers, amplifier output power: 12 x up to 100 Watt, Pan Pan Beam network I/O: 2 x etherCON RJ 45 for 2x analog line input, control data and error detection, PSU: 90...264 V AC, Connectors: powerCON TRUE 1 (input + link out), colour: RAL 9005 black structure	C3	
PB 224-AES/EBU	As PB 224 but with **2x AES/EBU** input instead of analog audio	C3	
PB 224-D	As PB 224 but with **DANTE** module, DANTE Primary and Secondary Port: 2x etherCON RJ 45 (2 x audio streams, control data), 1x etherCON: Pan Beam Net Link Port	C3	
PB 224-100V	As PB 224 instead of RJ 45 connectors: Pan Beam network I/O: 2 x Buccaneer: (**2 x 100 V input**, control data, fault relay)	C3	
PB 224-100V-DC input	As PB 224 instead of RJ 45 connectors: Pan Beam network I/O: 2 x Buccaneer: (**2 x 100 V input**, control data, fault relay), additional **DC input for 24 Volt DC** (Buccaneer)	C3	
PB 224-IP54	As PB 224 instead of RJ 45 connectors: Pan Beam network I/O: 2 x Buccaneer: (2 x 100 V input, control data, fault relay)	C3	
PB 224-AES/EBU-IP54	As PB 224- AES/EBU but with IP54 weather protection	C3	
PB 224-100V-IP54	As PB 224-100 V but with IP54 weather protection	C3	
PB 224-100V-DC input-IP54	As PB 224- 100 V-DC input but with IP54 weather protection	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – PB 248



PB 248	**Standard version:** Consits of two PB 224 modules and link kit	C3	
PB 248-AES/EBU	Consits of two PB 224 - **AES/EBU** modules and link kit	C3	
PB 248-D	Consist of PB 224-D Module + Slave Module and link kit	C3	
PB 248-100V	Consist of two PB 224 - **100 V** modules and link kit	C3	
PB 248-100V-DC input	Consits of two PB 224-100V-DC input	C3	
PB 248-IP54	Consits of two PB 224-IP 54	C3	
PB 248-AES/EBU-IP54	Consits of two PB 224-AES/EBU-IP54	C3	
PB 248-100V-IP54	Consits of two PB 224-100V-IP54	C3	
PB 248-100V-DC input-IP54	Consits of two PB 224-100V- DC input-IP54	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam – P SW-xxx Powered Subwoofer Series

	**P SW-208-SP**	Double 8" band-pass subwoofer, including DSP and amplifier. Frequency range: 42 Hz to 120 Hz, power: 300 watts (RMS), max SPL 128 dB, Pan Net I/O: 2 x etherCON (2 x analog line input, data and error detection), supply voltage: 90...264 V AC, connection type: 1 x IEC 60320-1 C13, housing: birch multiplex wood **standard colour: RAL 9005 black / textured finish**	C3	
	P SW-208-SP-AES/EBU	As P SW-208-SP with EtherCON RJ 45 for 2x **AES/EBU** mono input	C3	
	P SW-208-SP-D	As P SW-208-SP with **DANTE** Primary and Secondary Port: 2x EtherCON RJ 45 (2 x audio streams, controll data), 1x etherCON Pan Net Link Port	C3	
	**P SW-112-SP**	Single 12" bass reflex subwoofer including DSP and amplifier. Frequency range 35 Hz to 130 Hz, power: 2000 watts (RMS), max SPL 130 dB, Pan Net I/O: 2 x etherCON (2 x analog line input, data and error detection), 1 x NL4 - Link Out, supply voltage: 90 ... 264 V AC, connection type: 1 x powerCON TRUE1, housing: birch multiplex wood	C3	
	P SW-112-SP-AES/EBU	As P SW-112-SP with EtherCON RJ 45 for 2x **AES/EBU** mono input	C3	
	P SW-112-SP-D	As P SW-112-SP with **DANTE** Primary and Secondary Port: 2x EtherCON RJ 45 (2 x audio streams, controll data), 1x etherCON Pan Net Link Port	C3	
	**P SW-118-SP**	Single 18" bass reflex subwoofer including DSP and amplifier. Frequency range 35 Hz to 130 Hz, power: 2500 watts (RMS), max SPL 133 dB, Pan Net I/O: 2 x etherCON (2 x analog line input, data and error detection), 1 x NL4 - Link Out, supply voltage: 90 ... 264 V AC, connection type: 1 x powerCON TRUE1, housing: birch multiplex wood **standard colour: RAL 9005 black / textured finish**	C3	
	P SW-118-SP-AES/EBU	As PB S-118 with EtherCon RJ 45 for 2x **AES/EBU** mono input	C3	
	P SW-118-SP-D	As PB S-118 with **DANTE** module, DANTE Primary and Secondary Port: 2x EtherCon RJ 45 (2 x audio streams, controll data), Pan Beam Net Link Port	C3	

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Colour option (RAL-XXXX, powder coated, three gloss levels)





The painting refers to housing and grids in the same colour, different colours (housing, grid) are available on request.			
CO 04	Colour option RAL-xxxx for Px 04-x and Px 07-x	C3	185.–
CO 08	Colour option RAL-xxxx for Px 08-x and Px 15-x	C3	365.–
CO 16	Colour option RAL-xxxx for Px 16-x	C3	550.–
CO 24	Colour option RAL-xxxx for Px 24-x	C3	730.–
CO 32	Colour option RAL-xxxx for Px 32-x	C3	915.–
CO 40	Colour option RAL-xxxx for Px 40-x	C3	1‘100.–
CO 224	Colour option RAL-xxxx for Px 224	C3	550.–
CO 248	Colour option RAL-xxxx for Px 248	C3	1‘100.–
CO 261	Colour option RAL-xxxx for P 261	C3	285.–
CO wall mount	Colour option RAL-xxxx for wall mount or slider sets	C3	145.–
CO subwoofer	Colour option RAL-xxxx for subwoofer	C3	710.–
CO stand base	Colour option RAL-xxxx for stand base P/PB	C3	410.–
Default colour for all Pan Beam products is aluminium RAL 9006, or RAL-9010 (white) or RAL-9005 (black), unless another colour information is specified for a product. Usually all products are powdered. colour have to choose by order, with RAL xxxx (4-bit code) and gloss level. Other colour systems are possible, like RAL (3-bit code), NCS, Pantone, DB etc, on request.			

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Pan Beam Net - Interfaces

	**PanCon Blue**	Converter USB to PanBeamNet for setup and audio connection. Audioinput 2x XLR 3-Pin female connector for analog and digtial audiosignals (symmetric). Pan Beam Net connection (RJ 45)	C3	
	**PanSplitter 2/6**	Pan Beam 19" rack mount network switch, Connections: 2 x XLR female, USB (B), RS 485 (Phoenix), Outputs: 6 x EtherCon (Pan Beam network, incl. both Audiofeeds A and B), 1 x alarm contact, RS 485 input for media control, incl. Rack Mount	C3	
	**PanSplitter 4/4**	Pan Beam 19" rack mount network switch, Connections: 4 x XLR female, USB (B), RS 485 (Phoenix), Outputs: 4 x EtherCon (Pan Beam network, only one Audiofeed (A)), AES/EBU ready, 1 x alarm contact, RS 485 input for media control, incl. Rack Ears	C3	
	NEW! **Pan Net - Dante Interface**	Abgesetztes Pan Net Dante Interface für digitale Audio- und Steuerdaten zum Anschluss an externe DC Spannungsversorgung (20..36 VDC / 0,5 A), Hinweis: DC-Netzteil ist nicht im Lieferumfang enthalten.	C3	

Pan Beam Options

	**Pilottone evaluation**	22kHz Pilot-tone and fault signal contact, available for all Pan Beam units	C3	

Pan Beam Cables

	5m Bucaneer	Connector cable, 5m, 8-Pin Bulgin Buccaneer Coupling to RJ45 network connector (Art. 803274)	C3	
	10m Bucaneer	Connector cable, 10m, 8-Pin Bulgin Buccaneer Coupling to RJ45 network connector (Art. 803607)	C3	
	20m Bucaneer	Connector cable, 20m, 8-Pin Bulgin Buccaneer Coupling to RJ45 network connector (Art. 803606)	C3	
	5m Bucaneer	Connector cable, 5m, 8-Pin Bulgin Buccaneer Coupling to clutch on open end (Art. 802196)	C3	
	Terminator	Buccaneer Terminator (Art. 802268)	C3	

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

Accessories

	**fixed wall mount**	Wall-mount kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. (Art. 801839)	C3	90.–
	**rotable mall mount (TWM II)**	Swivel wall-mount kit for mounting Pan Column-Speaker on Wall (bottom and top) P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08 and PB 16 in stainless steel. (Art. 801840)	C3	135.–
	**horizontally rotable wall mount (TWM III)**	Wall-mount horizontal turnable kit for mounting Pan Column-Speaker on wall, PB 04, PB 08, P 04-Pi, P 08-Pi, P 8-15-Pi. 2 pcs for: PB 16 + PB 24, 3 pcs for: PB 32. (Art. 801841)	C3	175.–
	**stand holder P / PB xx**	Stand mount (35mm), stainless steel for: P 01-Pi, P 02-Pi, P 04-Pi, P 08-Pi, P 8-15-Pi, PB 04, PB 08, PB 16. (Art. 801843)	C3	200.–
	**slider set, PB xx MKII**	Slider set, consist of 2 x PB xx slider, to connect two PB xx together (Art. 801924)	C3	150.–
	**adaptor cover mounting PB xx**	For floor or ceiling mount (Art. 802459)	C3	120.–
	**spacer 50mm**	For wall mount, when using Buccaneer connections (IP65 and 100V versions) in combination with wall mount 801839 or 801841, stainless steel (Art. 802822)	C3	55.–
	**turnable wall mount TWM IV black**	Turnable Wall Mount for P/PB 2xx incl. mounting kit 800388. The wall mount enables horizontal orientation included, **colour: black** (Art. 804927). 1 pc per P 261-AMT, 2 pcs per PB 224.	C3	245.–
	**turnable wall mount TWM IV white**	Turnable Wall Mount for P/PB 2xx incl. mounting kit 800388. The wall mount enables horizontal orientation included, **colour: white** (Art. 804926). 1 pc per P 261-AMT, 2 pcs per PB 224.	C3	245.–
	**turnable wall mount TWM IV steel**	Turnable Wall Mount for P/PB 2xx incl. mounting kit 800388. The wall mount enables horizontal orientation included, **colour: steel** (Art. 804928). 1 pc per P 261-AMT, 2 pcs per PB 224.	C3	245.–
	**mounting plate, PB 2xx WMP**	PB 224, wall mount kit, consist of adapter plate and 2 x PB 224 slider (Art. 800388)	C3	110.–
	**stand holder P/PB xxx**	Stand mount (35mm) for P/PB xxx (Art. 800392)	C3	235.–
	**adaptor cover mounting PB 224**	For floor or ceiling mount (Art. 802858)	C3	200.–
	**slider set, PB 2xx**	Connection kit, consist of 4 x PB 224 slider, to connect two PB 224 together (Art. 800393)	C3	185.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

	**Stand base P/PB**	High-quality base with shapely steel base plate 450x450 mm. P / PB xx loudspeakers [consisting of a maximum of two modules (P/PB 08 / PB 15)] can be mounted on the base. The base has a grid in the base plate to align the base including loudspeakers horizontally in 15-degree steps. The rear-mountable cable duct ensures protected wiring. The base plate can be leveled using four adjustable feet. The front grille design of the base corresponds to that of the Pan Beam & Pan Speaker series, the lowest grid element is interchangeable. Available colours: RAL 9005 (black), RAL 9010 (white	C3	1‘920.–
	PB 2xx grid	Grid to fly up to 5 PB 224 modules (Art. 802991)	C3	875.–
	PB 2xx flyware	Flyware für PB 224 (Art. 802992)	C3	1‘165.–
	**wall mount, tiltable, turnable (black)**	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, colour: RAL 9005 black (Art. 801449)	C3	95.–
	**wall mount, tiltable, turnable (white)**	Universal wall mount (horizontal 180° and vertical 0-15° adjustment), up to 10 kg load, incl. Sliding block, **standard colour: white** (art. 801450)	C3	95.–
	**Rain Hood Px 208**	Weather protection fabric for outdoor use. Suitable for bass speakers: PB S-208 and P S-208 (Art. 802163)	C3	295.–
	**Rain Hood Px 118**	Weather protection fabric for outdoor use. Suitable for bass speakers: PB S-118 and P S-118 (Art. 802195)	C3	365.–
	**pole mount PBxx**	Mounting bracket for P/PB 08, PB 16, on poles (art. 802370), stainless steel. Note: Tension straps for attaching to the mast are not included in the bracket.	C3	465.–
	**Speaker tilt connector „RingLock“**	For speaker stands with tube diameter of 35 mm. A unique patented expanding mandrel system provides a tight and firm fit for the speaker. The moveable plastic splints separate the speaker from the standcreating a vibration-free connection. Easy to use ring lock. Colour black (art. 802349).	C3	115.–
	**speaker stand with plate RingLock (black)**	speaker stand with patented expanding mandrel system that provides a stable, tight and firm fit for speakers. Connecting the speaker is easy and is done using the handy ring lock - which is simply placed in position and screwed on. Heavy cast iron plate with a relatively small diameter. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. Max. height 1.800 mm, suitable for speakers with max. 20 kg. **standard colour: black** (art. 801488)	C3	245.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

	**speaker stand with plate (white)**	A decorative space saving speaker stand. The heavy cast iron plate with a relatively small diameter requires little space. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. The stand has a maximum pull-out height of 1800 mm and is suitable for speakers with a maximum weight of 20 kg. The integrated mounting aid simplifies mounting the loud speaker cabinets. **standard colour: white** (art. 801580)	C3	185.–
	**speaker stand with plate (black)**	A decorative space saving speaker stand. The heavy cast iron plate with a relatively small diameter requires little space. The tried-and-tested spring-loaded bolt with locking screw makes height adjustment easy and safe. The stand has a maximum pull-out height of 1800 mm and is suitable for speakers with a maximum weight of 20 kg. The integrated mounting aid simplifies mounting the loud speaker cabinets. **standard colour: black** (art. 801581)	C3	185.–
	**ceiling mount, fix, (white) PB xx**	Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45 °. Within the parameters - the settings range from 0 to 45°. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, colour: **standard colour: white** (art. 801452)	C3	175.–
	**ceiling mount, fix, (black) PB xx**	Robust and useful loudspeaker ceiling mount with 250 mm distance and internal cable management. The swivel area is +/- 45 °. Within the parameters - the settings range from 0 to 45°. Max. load ais 25kg. The clamping bracket is for loudspeakers with a vertical mounting template from 70 to 76.2 mm. For other attachment possibilities additional adapter brackets are available. A mounting bracket with side and central cable management makes mounting to the ceiling easier. incl. slider block, **standard colour: black** (art. 801451)	C3	175.–
	**ceiling mount, flex, (black) PB xx**	Flexible ceiling mount with variable length 700-1200mm incl. slider block, standard colour: black (art. 802406)	C3	380.–
	**ceiling mount, flex, (white) PB xx**	Flexible ceiling mount with variable length 700-1200mm incl. slider block, **standard colour: white** (art. 801285)	C3	380.–
	**P 261-AMT Array Bracket 20°**	Angle adapter in stainless steel for mounting 2 x P 261-AMT loudspeakers (H-version) at a 20° angle. Note: An appropriate wall/ceiling mount is required for wall/ceiling mounting.	C3	280.–

GO WILD AG
Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05

	**VESA Speaker Mount VSM (55" - 65")**	Vario adapter for mounting speakers re/li from the display, is mounted between VESA holder and display. For display sizes from 55" - 65", colour: RAL 9005	C3	470.–
	**VESA Speaker Mount VSM (75" - 98")**	Vario adapter for mounting speakers re/li from the display, is mounted between VESA holder and display. For display sizes from 75" - 98", colour: RAL 9005	C3	585.–

Ersetzt alle bisherigen Preislisten.
Remplace toutes les listes de prix anciennes.

Artikel mit grau unterlegtem Händlercode sind Neuheiten oder haben eine Preisänderung erfahren.
Articles avec code client gris sont des nouveautés ou ont changé de prix.

Bei Artikeln mit unterstrichenem Händlercode bitte Verfügbarkeit anfragen!
Articles avec code client souligné demandez leur disponibilité!

Sumpfstrasse 22 • 6312 Steinhausen • Tel 041 766 37 00
e-mail: info@gowild.ch • www.gowild.ch • FAX 041 766 37 05